

The drawing shows a machine guideway assembly with the following details:

- Top View:** Shows the overall layout with dimensions CM+46, CM, and 46. It includes a surface texture symbol $Ra\ 3.2$ and a surface finish symbol $\sqrt[0.1]{0.1G}$. A vertical dimension of 15.05 is shown on the left.
- Front View:** Shows the profile of the assembly with dimensions 8, 650, 70, 650, and 8. It includes a surface texture symbol $\sqrt[0.1]{0.1/1000}$ and a surface finish symbol $\sqrt[0.2]{G}$. A dimension of 3.5±0.5 is shown for a curved section.
- Side View:** Shows the side profile with dimensions 23.5±0.1, 50, and nx50. It includes a note "Code start value: 100mm".
- Detail Views:** Two detail views of the assembly are shown, one with dimensions 4.7, 9, 3, 40±0.1, 3, and 46, and another with dimensions 19, 12, and 4.7.
- Legend:** CM = Curso medición, CM = Measuring length, G = Guía máquina, G = Machine guideway.
- Table:** A table with 5 columns: N°, Designación, Cant., Material, and Acabado. It contains 5 rows of data.
- Scale:** Escala: Resto Tolerancias s/norma ISO 2768-mK. The table includes tolerance values for different dimensions.
- Footer:** The drawing is dated 05-10-16 and is drawn by SORMEN. It is a technical drawing of a machine guideway assembly.

CM= 1340

FAGOR 