

The drawing shows a machine guideway assembly with the following details:

- Top View:** Shows the overall layout with dimensions CM+46, CM, and 46. It includes a surface finish symbol $Ra\ 3.2$ and a tolerance box $\begin{matrix} \square & 0.1 \\ \parallel & 0.1G \end{matrix}$.
- Front View:** Shows the profile of the assembly with dimensions 15.05, 0.35±0.1, 0.2/50, 3.5±0.5, 30, 0.1/1000, 1, 70, 200, 8, CM+30, and 46. It also includes a tolerance box $\begin{matrix} \square & 0.2G \end{matrix}$.
- Side View:** Shows the side profile with dimensions 8, 200, 70, 200, 8, and CM+30. It includes a tolerance box $\begin{matrix} \square & 0.1/1000 \end{matrix}$.
- Detail Views:** Includes a detail of the end of the guideway with dimensions 4.7, 9, 3, 40±0.1, 3, and M3 L<5. Another detail shows a cross-section with dimensions 19, 12, and a hole.
- Assembly Notes:** CM = Curso medición (Measuring length), CM = Measuring length, G = Guía máquina (Machine guideway), G = Machine guideway.
- Table:** A table with 5 columns: N°, Designación, EXG_EXGA-440, Cant., Material, and Acabado. It includes a row for the assembly and a row for the material.
- Scale:** Escala: Resto Tolerancias s/norma ISO 2768-mK. The table also includes a row for the scale and a row for the material.

						Escala: Resto Tolerancias s/norma ISO 2768-mK $\begin{array}{l l} < 5 \pm 0,1 & 50 - 100 \pm 0,4 \\ 5 - 25 \pm 0,15 & > 100 \pm 0,6 \\ 25 - 50 \pm 0,2 & \alpha^\circ \pm 30' \end{array}$
Nº	Modificado			Propu.	Vº Bº	Fecha
				Entre ejes $\pm 0,25$		
		1			Acabado	
Nº	Designación	EXG_EXGA-440	Cant.	Material	Tratamiento	
Plano Nº		El 05-10-16		Fagor Automation S. Coop. 20500 Mondragón		
Sustituye a:		Dibujado SORMEN				
		Comprobado				

FAGOR 