

The drawing shows a machine guideway assembly with the following details:

- Top View:** Shows the overall layout with dimensions CM+46, CM, and 46. It includes a surface texture symbol $Ra\ 3.2$ and a tolerance box $\begin{matrix} \square & 0.1 \\ \parallel & 0.1G \end{matrix}$.
- Front View:** Shows the profile of the guideway with dimensions 15.05, 0.35±0.1, 0.2/50, 3.5±0.5, 30, 0.1/1000, 1, 70, 450, 8, CM+30, and 46. It also includes a tolerance box $\begin{matrix} \square & 0.2G \end{matrix}$.
- Side View:** Shows the side profile with dimensions 8, 450, CM+30, 70, 450, 8, and 46. It includes a tolerance box $\begin{matrix} \square & 0.1 \\ \parallel & 0.1G \end{matrix}$.
- Detail Views:** Two detail views of the end of the guideway. The first detail view shows dimensions 4.7, 9, 3, 40±0.1, 3, and 12. The second detail view shows dimensions 2.5, 14±0.1, 2.5, 3, 40±0.1, 3, and 46. Both detail views include a tolerance box $\begin{matrix} \square & 0.1 \\ \parallel & 0.1G \end{matrix}$.
- Assembly Notes:** CM = Curso medición (Measuring length), CM = Measuring length, G = Guía máquina (Machine guideway), G = Machine guideway.
- Table:** A table with 5 columns: N°, Designación, EXG_EXGA-940, Cant., Material, and Acabado. The table contains 5 rows of data.
- Scale:** Escala: Resto Tolerancias s/norma ISO 2768-mK. The table also includes a section for "Entre ejes ± 0.25".
- Footer:** The footer contains the text "FAGOR" and "FAGOR Automation S. Coop. 20500 Mondragón".

CM= 940

FAGOR 